


BASIC RATED DYNAMIC LOAD (kgf)	765
BASIC RATED STATIC LOAD(kgf)	1240
THREAD DIR. /NO. OF START THD	RIGHT/ 1
BCD (mm)	$\phi 16.545$
LEAD (mm)	5
BALL DIA.(mm)	$\phi 3.175$
ROOT DIA.	$\phi 19.72$
EFFECTIVE TURNS (CIRCUIT:ROW)	1X3
LEAD ANGLE	5.5°

Ball Nut Dwg		FDUD1605T3DV00	
TOLERANCES FOR REGULAR DIMENSIONS (MM)			
RANGE	TOLERANCE	RANGE	TOLERANCE
0.5-6	$\pm 0.1$	401-1000	$\pm 0.8$
7-30	$\pm 0.2$	1001-2000	$\pm 1.2$
31-120	$\pm 0.3$	2001-4000	$\pm 2.0$
121-400	$\pm 0.5$	4001 OVER	$\pm 3.0$
NO.		DATE	DESCRIPTION
DESIGNER		DRAW	
CHECK		APPROVE	
DATE		98-03-19	

CUSTOMER: ZAPP (英國)  
 SPEC=R16-05T3-1-FDUD-519-600-0.05-R-P1

(註: 未標之倒角皆為C1) NOT EFFECTIVE HARDENED AREA (不在有效熱處理範圍內)  
 Note: Chamferings are C1 if not specified otherwise



DRAW	陳有成
CHECK	李
APPROVE	李
DATE	98-03-19

GTEN BALL SCREW TECHNOLOGY

DWG NO.	9B1806
CUSTOMER'S DWG. NO.	
SCALE	1:X

AXIAL PLAY	
DRAG CENTER	0
TORQUE RANGE (kgf-cm)	0
SPRING FORCE (kgf)	0
THREAD PROFILE	GOthic
MATERIAL	S55C
SCREW NUT	SCM415H
HARDNESS	HRC58'-62'
熱處理	熱處理